

Custom Forklift Spur Gear for Material Handling Drive Trains

Built for stop-start shock loading and long wear life, with consistent fit across repeat production batches.



ISO 1328 Grade 6-8
Hardness HRC 58-52




OEM / DFM Support



Superior Meshing Stability

Controlled lead and tooth profile for lower vibration, lower noise, and more stable meshing.



Enhanced Material Durability

Heat-treated steel options for higher wear resistance, fatigue strength, and service life.



Transparent Quality Traceability

Inspection reports support quality records and batch traceability.

Item	Specification	Typical	Notes
Module	1 - 5	2 - 4	As drawing
Pressure Angle	15 – 25°	20°	As drawing
Process	Forging / Broaching / Grinding / Hobbing / Shaping / Shaving / Milling	Grinding / Shaping	As drawing
Materials	20CrMnTi / 8620H / 20CrMo / 40Cr / 42CrMo / 45#steel / Others	20CrMnTi	As drawing
Heat Treatment	Carburized & Quenched / Q&T / Nitrided	Carburized	As drawing



Drawing Review:
Fast response & DFM feedback to evaluate manufacturability.



Process Recommendation:
Optimization of manufacturing routes based on requirements.



Prototype to Production:
From single sample to mass production lots, Meet the demands.



Final QC & Export:
Export-ready packaging and full QC documentation.

Ready to custom your forklift gear ?
Send your drawing a quick evaluation

Email: sales@wenlio.com

WhatsApp: +86 18257981010

Web: www.wenlio.com